

[Sign In](#) | [My EndNote Web](#) | [My ResearcherID](#) | [My Citation Alerts](#) | [My Saved Searches](#) | [Log Out](#) | [Help](#)

ISI Web of Knowledge™

Web of Science

Additional Resources

[Search](#) [Cited Reference Search](#) [Advanced Search](#) [Search History](#) [Marked List \(0\)](#)

Web of Science®

<< [Back to results list](#)

Record 9 of 10

Record from Web of Science®

Modeling flux decline during nanofiltration of NOM with poly(arylsulfone) membranes modified using UV-assisted graft polymerization

[Print](#) [E-mail](#) [Add to Marked List](#) [Save to EndNote® Web](#)
[Save to EndNote®, RefMan, ProCite](#) [more options](#)

Author(s): [Kilduff JE](#), [Mattaraj S](#), [Sensibaugh J](#), [Pieracci JP](#), [Yuan YX](#), [Belfort G](#)

Source: ENVIRONMENTAL ENGINEERING SCIENCE **Volume:** 19 **Issue:** 6 **Pages:** 477-495 **Published:** NOV-DEC 2002

Times Cited: 19 **References:** 38 [Citation Map](#)

Abstract: Poly(ether sulfone) and sulfonated poly(sulfone) nanofiltration membranes were modified by UV irradiation and UV-assisted graft polymerization of N-vinyl-2-pyrrolidinone (NVP) as a strategy for increasing the wettability of membrane surfaces and mitigating fouling by naturally occurring organic compounds present in surface waters. The UV-assisted graft polymerization approach with 3% NVP and a reaction time of 60 s increased the wettability (increased $\cos \theta$) of membrane surfaces, which exhibited a significantly lower propensity to foul. For these conditions, clean water permeability and solute rejection (as organic carbon) were maintained close to that of the as-received membranes. Graft polymerization was carried out using two different methods. With the dip method, membrane coupons coated with a 3% N-vinyl-2-pyrrolidinone solution were UV irradiated under nitrogen. With the immersion method, membrane coupons were irradiated directly in nitrogen-purged 3% NVP solution. Both techniques increased membrane wettability; however, the immersion technique required much longer reaction times resulting from the absorption of UV radiation by the monomer solution. Flux decline of modified membranes was well described using a combined pore blockage/cake filtration model that was modified to incorporate back-transport. Model results provide support for the interpretation that the enlargement of the membrane pore structure caused by long irradiation times allowed additional pore fouling by larger molecular weight natural organic matter components that were previously rejected.

Document Type: Article

Language: English

Author Keywords: fouling; membrane separations; water treatment; surface modification; nanofiltration

KeyWords Plus: NATURAL ORGANIC-MATTER; HUMIC-ACID; ULTRAFILTRATION MEMBRANES; REVERSE-OSMOSIS; PHOTOCHEMICAL MODIFICATION; POLY(ETHER SULFONE);

Cited by: 19

This article has been cited 19 times (from Web of Science).

[Rana D, Matsuura T](#) [Surface Modifications for Antifouling Membranes](#) CHEMICAL REVIEWS 110 4 2448-2471 APR 2010

[Dang HT, Rana D, Narbaitz RM, et al.](#) [Key Factors Affecting the Manufacture of Hydrophobic Ultrafiltration Membranes for Surface Water Treatment](#) JOURNAL OF APPLIED POLYMER SCIENCE 116 5 2626-2637 JUN 5 2010

[Tomer N, Mondal S, Wandera D, et al.](#) [Modification of Nanofiltration Membranes by Surface-Initiated Atom Transfer Radical Polymerization for Produced Water Filtration](#) SEPARATION SCIENCE AND TECHNOLOGY 44 14 3346-3368 2009

[[view all 19 citing articles](#)]

[Create Citation Alert](#)

Related Records:

Find similar records based on shared references (from Web of Science).

[[view related records](#)]

References: 38

View the bibliography of this record (from Web of Science).

Suggest a correction

If you would like to improve the quality of this product by suggesting corrections, [please](#)

IONIC-STRENGTH; GROUND WATERS; MICROFILTRATION;
FILTRATION

[fill out this form.](#)

Reprint Address: Kilduff, JE (reprint author), Rensselaer Polytech Inst, Dept Civil & Environm Engr, 110 8th St,5049 JEC, Troy, NY 12180 USA

Addresses:

1. Rensselaer Polytech Inst, Dept Civil & Environm Engr, Troy, NY 12180 USA
2. Rensselaer Polytech Inst, Howard P Isermann Dept Chem Engr, Troy, NY 12180 USA

Publisher: MARY ANN LIEBERT INC PUBL, 2 MADISON AVENUE, LARCHMONT, NY 10538 USA

Subject Category: Engineering, Environmental; Environmental Sciences

IDS Number: 635JT

ISSN: 1092-8758

[<< Back to results list](#)

◀ Record 9 of 10 ▶

Record from **Web of Science®**

Output Record

Step 1:

- Authors, Title, Source
 plus Abstract
 Full Record
 plus Cited Reference

Step 2:

[\[How do I export to bibliographic management software?\]](#)

[Print](#) [E-mail](#) [Add to Marked List](#)
[Save to EndNote® Web](#) [Save to EndNote®, RefMan, ProCite](#)
 Save to other Reference Software [Save](#)

View in [简体中文](#) [English](#) [日本語](#)

Please give us your [feedback](#) on using ISI Web of Knowledge.

[Acceptable Use Policy](#)
 Copyright © 2010 Thomson Reuters



THOMSON REUTERS

Published by Thomson Reuters