Sign In | My EndNote Web | My ResearcherID | My Citation Alerts | My Saved Searches | Log Out | Help | S | Web of Krowledge

Web of Science



Additional Resources

Search

Cited Reference Search

Advanced Search

Search History

Marked List (0)

Web of Science®

<< Back to results list

■ Record 10 of 10 ■

Record from Web of Science®

An apparatus to measure gas permeability of geosynthetic clay liners

Print E-mail Add to Marked List Save to EndNote Web

Save to EndNote, RefMan, ProCite more options

Author(s): Bouazza A, Vangpaisal T

Source: GEOTEXTILES AND GEOMEMBRANES Volume: 21 Issue: 2 Pages: 85-101 Published: APR 2003

Abstract: This paper describes a test device and test method for measuring the gas permeability of partially saturated geosynthetic clay liners. The tests were carried out on a commercially available needle punched geosynthetic clay liner (GCL). The GCL samples were partially hydrated with de-ionized water for 7-10 days under zero confinement and 20 kPa surcharge, respectively, prior to testing. Measurements of the differential pressure across the GCL samples at varying flow rates were used to calculate gas permeability at different gravimetric moisture contents. The differential pressure used in the present investigation ranged from 1 to 40 kPa. The highest pressures (> 0 kPa) were used to verify the validity of Darcy's equation. The results highlighted the influence of moisture content on gas flow kinetics and also showed that the apparatus can provide a reliable and simple method of measuring gas permeability. For the GCL and conditions examined, it was found that the intrinsic permeability decreased as the volumetric moisture content increased. More importantly it was found that the pre-hydration curing process could affect the intrinsic permeability. Higher intrinsic permeabilities (when volumetric water content >40%) were obtained when the moisture was not distributed uniformly. (i.e. for samples pre-hydrated under no confinement). At lower volumetric water content (<40%) the pre-hydrating conditions did not seem to affect the intrinsic permeability values simply because there was less water available for further hydration. (C) 2003 Elsevier Science Ltd. All rights reserved.

Document Type: Article

Language: English

Author Keywords: apparatus; hydration; gas permeability;

geosynthetic clay liner; moisture effect

KeyWords Plus: GCL HYDRAULIC CONDUCTIVITY; POROUS-

MEDIA; FLOW

Reprint Address: Bouazza, A (reprint author), Monash Univ, Dept

Civil Engn, POB 60, Melbourne, Vic 3800 Australia

Addresses

1. Monash Univ, Dept Civil Engn, Melbourne, Vic 3800 Australia

Cited by: 21

This article has been cited 21 times (from Web of Science).

Mendes MJA, Pierson P, Touze-Foltz N, et al. Characterisation of permeability to gas of geosynthetic clay liners in unsaturated conditions GEOSYNTHETICS INTERNATIONAL 17 5 344-354 OCT 2010

Bonhomme C, Beaudet-Savignat S, Chartier T, et al. Elaboration, by tape casting, and thermal characterization of a solid oxide fuel half-cell for low temperature applications MATERIALS RESEARCH BULLETIN 45 4 491-498 APR 2010

Barral C, Oxarango L, Pierson P Characterizing the Gas Permeability of Natural and Synthetic Materials TRANSPORT IN POROUS MEDIA 81 2 277-293 JAN 2010

[view all 21 citing articles]

Create Citation Alert

Related Records:

Find similar records based on shared references (from Web of Science).

[view related records]

References: 26

View the bibliography of this record (from Web of Science).

Suggest a correction

If you would like to improve the

2. Ubon Ratchathani Univ, Dept Civil Engn, Ratchathani 34190, Thailand

Publisher: ELSEVIER SCI LTD, THE BOULEVARD, LANGFORD LANE, KIDLINGTON, OXFORD OX5 1GB, OXON, ENGLAND

Subject Category: Engineering, Geological; Geosciences,

Multidisciplinary

IDS Number: 653BL ISSN: 0266-1144

quality of this product by suggesting corrections, please fill out this form.



Please give us your feedback on using ISI Web of Knowledge.

Acceptable Use Policy Copyright © 2010 Thomson Reuters



Published by Thomson Reuters