Web of Science



Additional Resources

Search Cited Reference Search Advanced Search Search History

Web of Science®

< Back to results list

Record 7 of 8

Record from Web of Science®

Characteristics of impact driven supersonic liquid jets

Print E-mail Add to Marked List Save to EndNote Web

Save to EndNote, Ref Man, ProCite more options

Author(s): Pianthong K, Zakrzewski S, Behnia M, Milton BE

Source: EXPERIMENTAL THERMAL AND FLUID SCIENCE Volume:

27 Issue: 5 Pages: 589-598 Published: MAY 2003

Abstract: In this paper, a technique for the generation of supersonic liquid (water and diesel fuel) jets is presented. The supersonic liquid jet is generated by the use of a purpose-developed vertical, single-stage powder gun. The characteristics and behavior of supersonic liquid jets were obtained by visualization using the shadowgraph technique. The visual evidence related to supersonic liquid jets (velocity around 2000 m/s) generated from a variety of nozzle types is presented and the effects of nozzle parameters on the jet behavior are described. The characteristics of the leading edge shock wave and jet shape were found to be significantly related to the nozzle geometry. A one-dimensional analysis of the multiple, reflected shock waves inside the liquid sac and nozzle during the process of supersonic jet generation is presented. The method allows impact pressure, particle velocity and effect of shock wave reflections inside the nozzle cavity on the liquid jet velocity to be obtained. Jet shock waves obtained from the shadowgraph image and CFD simulation are also compared, The jet outflow characteristics and its leading edge shock wave in air were assessed for their potential for auto-ignition using fuel with cetane numbers from 50-100. The contribution of the strong leading edge shock wave to the auto-ignition is discussed. (C) 2003 Elsevier Science Inc. All rights reserved.

Document Type: Proceedings Paper

Language: English

Author Keywords: supersonic liquid jets; jet shock wave; shadowgraph

visualization

 $\textbf{Reprint Address:} \ \textbf{Behnia}, \ \textbf{M} \ (\textbf{reprint author}), \ \textbf{Univ New S Wales}, \ \textbf{Sch}$

Mech & Mfg Engn, Sydney, NSW 2052 Australia

Addresses:

1. Univ New S Wales, Sch Mech & Mfg Engn, Sydney, NSW 2052 Australia

Publisher: ELSEVIER SCIENCE INC, 360 PARK AVE SOUTH, NEW YORK, NY 10010-1710 USA

Cited by: 6

Marked List (0)

This article has been cited 6 times (from Web of Science).

Lu ZH, Shaikh TR, Barnard D, et al. Monolithic microfluidic mixingspraying devices for timeresolved cryo-electron microscopy JOURNAL OF STRUCTURAL BIOLOGY 168 3 388-395 DEC 2009

Estruch D, Lawson NJ, Garry KP Application of Optical Measurement Techniques to Supersonic and Hypersonic Aerospace Flows JOURNAL OF AEROSPACE ENGINEERING 22 4 383-395 OCT 2009

Kim HD, Lim CM, Lee HJ, et al. A study of the gas flow through air jet loom JOURNAL OF THERMAL SCIENCE 16 2 159-163 APR-JUN 2007

[view all 6 citing articles]

Create Citation Alert

Related Records:

Find similar records based on shared references (from Web of Science).

[view related records]

References: 18

View the bibliography of this record (from Web of Science).

1/12/2553 ISI Web of Knowledge [v.4 10] - Web... **Subject Category:** Thermodynamics; Engineering, Mechanical; Physics,

Fluids & Plasmas

IDS Number: 670DN

ISSN: 0894-1777

DOI: 10.1016/S0894-1777(02)00273-X

Suggest a correction

If you would like to improve the quality of this product by suggesting corrections, please fill out this form.



< < Back to results list	■ Record 7 of 8 ■	Record from Web of Science
Output Record		
Step 1:	Step 2: [How do I export to bibliographic n	nanagement software?]
Authors, Title, Sourceplus Abstract	Print E-mail Add to Marked List Save to EndNote, RefMan, ProCite	Save to EndNote Web
Full Record	Save to other Reference Software	Save
plus Cited Reference		
View in 简体中文 English 日本語		

Please give us your feedback on using ISI Web of Knowledge.

Acceptable Use Policy
Copyright © 2010 Thomson Reuters

